



HIGH PERFORMANCE BUILDING

DOWSIL™ Membrane Dual, DOWSIL™ Outside and DOWSIL™ 300 Adhesive

DOWSIL™ Membrane Dual / DOWSIL™ Membrane Outside

A choice of two new high performance EPDM membranes from Dow act as a vapor control, according to EN 13984, making them ideal for creating interior or exterior weather and air-tight seals. Bonded and secured using DOWSIL™ 300 Adhesive, DOWSIL™ Membranes are easy to use and provide a safe, compatible and durable system package which complements the DOWSIL™ range of high performance sealants.

DOWSIL™ Membrane Dual provides a weather- and air-tight seal in fenestration applications and can also be used to seal across adjacent building elements.

Features and benefits

- Very good mechanical properties
- Flexible and tear resistant
- Excellent movement capability, thus able to sustain thermal and structural movements of a building
- Resistant to UV light, temperature extremes, chemical pollutants and moisture
- Available in different widths to enable quick and easy installation
- High quality EPDM raw materials from Dow

Available dimensions

- DOWSIL™ Membrane Dual is available in log roll lengths of 25 m in a choice of 0.6 mm, 1.2 mm and 1.5 mm thickness in widths of 100 mm, 150 mm, 200 mm, 250 mm, 300 mm, 350 mm and 1.4 m.
- DOWSIL™ Membrane Outside 0.6 is available in log rolls of 25 m in 0.6 mm thickness in widths of 100 mm, 150 mm, 200 mm, 250 mm, 300 mm, 350 mm and 1.4 m.
- DOWSIL™ 300 Adhesive is supplied in 600 ml foil packs.

For further information, please refer to the DOWSIL™ Membrane Dual technical datasheet and the DOWSIL™ Membrane Outside 0.6 technical datasheet.



ideally the inner membrane shall have a higher s_d

s_d value),

Contact us

Dow is collaborating with industry professionals around the world to develop solutions to improve the world.

Images: GettyImages-187097170, dow_41162810359, dow_49971882369

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.